# CORONA PLUS REMOTE

### **Tuned by Carl Zeiss**

#### **Product description**

CORONA PLUS REMOTE is a complete spectrometer system available in a single-beam or dual-beam configuration. The measuring heads are connected to the front of the CORONA PLUS REMOTE sensor unit using fiber optics. On the dual-beam instrument, the connections for the measuring and reference channel are connected also to the front. The computer required for the evaluation can be connected via the ethernet interface. Both versions of the instrument run on 12 V DC. Furthermore, an external illumination source for the measuring heads can be connected via a 5volt output.

#### Areas of application

CORONA PLUS REMOTE is used to measure optical properties such as reflectance, transmission, color and coating thickness. These instrument systems have been designed for complex and fast measurements in quality and process monitoring under industrial conditions. Robust and extremely reliable, they are ideal for monitoring the production of architectural and automotive glass, plastics and coatings and the manufacture of solar cells. Furthermore, CORONA PLUS REMOTE is the system of choice for all applications in which speed and performance count.



The next generation in the compact class



We make it visible.

# **Technical Specifications**

	CORONA PLUS REMOTE VIS DB	CORONA PLUS REMOTE VIS SB	CORONA PLUS REMOTE VIS-NIR DB	CORONA PLUS REMOTE VIS-NIR SB
	for use with external heads like OFR and OFT	for use with external heads like OMK 500 or collimated optics	for use with external heads like OFR and OFT	for use with external heads like OMK 500 or collimated optics
Spectrometer	Double-beam diode array	Single-beam diode array	Double-beam diode array	Single-beam diode array
Polychromator	2 x MMS	MMS	2 x MMS 2 x PGS	1 x MMS 1 x PGS
Measurement range	380-1000 nm	380–1000 nm	380-1680 nm	380–1680 nm
Mean Spectral Pixel Pitch	3 nm	3 nm	3 nm	3 nm
Spectral resolution	≤ 10 nm	≤ 10 nm	≤ 10 nm	≤ 10 nm
Wavelength accuracy	≤ 1 nm	≤ 1 nm	≤ 1 nm	≤ 1 nm
Wavelength reproducibility	≤ 0,1 nm	≤ 0,1 nm	≤ 0,1 nm	≤ 0,1 nm
Light source	extern	extern	extern	extern
Internal protection standard	IP 65	IP 65	IP 65	IP 65
Dimensions	230 x 200 x 110	230 x 200 x 110	330 x 230 x 110	330 x 230 x 110
Weight	3.6 kg	3.6 kg	6.0 kg	6.0 kg
Range of operating temperature	5–45 °C	5–45 °C	5–45 °C	5–45 °C
Supply Voltage	9-36 V	9-36 V	9-36 V	9-36 V



### **Carl Zeiss MicroImaging GmbH** 07740 Jena, Germany

Industrial | Jena Location Phone: + 49 3641 64 2838 Telefax: + 49 3641 64 2485 E-Mail: info.spektralsensorik@zeiss.de

### www.zeiss.de/spectral

Example application

light measurement

(No. DE 10010213A1)

## **SCA Pacific Pte Ltd**

Block 108 Ang Mo Kio Ave 4, #01-88 Singapore 560108 Phone : + 65 6298 9989 Telefax :+ 65 6291 9989 : scapacific@singnet.com.sg E-Mail

## www.scapacific.com.sg



Information subject to change. Printed on environmentally friendly paper bleached without chlorine. 72-1-0004/e – printed 05.10